

# Washer extractor

## QuickWash QWC

### Features and benefits

- Control knob for simple program selection and start
- Large, clear display
- **AS – Automatic Savings:**
  - The machine weighs the linen and adjusts the amount of water and energy according to the load. This leads to considerable savings in case the machine is not fully loaded
- Four compartment detergent box for manual dosing of powder or liquid detergent
- High extraction force for efficient dewatering
- Panels and frame made from galvanized steel
- Inner and outer drums made from stainless steel
- Powder coated black front panel, side panels and top cover
- Strong door and hinges. Easy-grip, ergonomic door handle which makes the door easy to open and close
- Drain pump
- Frequency-controlled motor with no carbon or brushes
- Door seal in the door, does not wear when the machine is loaded and unloaded



Images shown are a representation of the product only and variations may occur.

### Main options

- Stacking kit to install tumble dryer QuickDry QDC on top to save space
- Plinths for raising the machine to a comfortable height (height 100 mm when installed with a tumble dryer, or 290 mm)
- Connecting hoses

| Main specifications                     |          | QuickWash QWC   |
|---|----------|-----------------|
| Max. capacity                           | kg       | 5.5             |
| Drum, volume                            | litre    | 53              |
|   | diameter | Ø mm            |
| Extraction                              | rpm      | 1300            |
| G-factor                                |          | 425             |
| Heating alternatives, electricity       | kW       | 2.2 / 2.8 / 4.4 |
| <b>Consumption data "Normal 60°C" *</b> |          |                 |
| Total time                              | min      | 38 / 49 / 44    |
| Water consumption                       | litre    | 56              |
| Energy consumption (motor/heating)      | kWh      | 0.15/0.80       |

\* Water temperature 15°C cold water.

| Electrical connections* |              |       |                  |                |                    |
|-------------------------|--------------|-------|------------------|----------------|--------------------|
| Heating alternative     | Main voltage |       | Heating power kW | Total power kW | Recommended fuse A |
|                         |              | Hz    |                  |                |                    |
| Electric heated         | 220-240V 1-  | 50/60 | 2.2              | 2.6            | 16                 |
|                         | 220-240V 1-  | 50/60 | 2.8              | 3.1            | 13                 |
|                         | 380-415V 3-  | 50/60 | 4.4              | 4.8            | 10                 |

| Water connections   |                       | QuickWash QWC |                       |
|---|-----------------------|---------------|-----------------------|
| Water valves  | DN                    | 20            |                       |
| Water pressure  | kPa                   | 200-500       |                       |
| Capacity at 300 kPa   | l/min                 | 17            |                       |
| Draining capacity   | l/min                 | 25            |                       |
| Max. draining   | l                     | 20            |                       |
| Floor requirements  |                       |               |                       |
| Frequency of the dynamic force  | Hz                    | 20            |                       |
| Floor load at max extraction  | kN                    | 1.02 ± 0.3    |                       |
| Sound levels  |                       |               |                       |
| Sound power level (IEC 60704-2-4)   |                       |               |                       |
| wash  | dB(A)                 | 59            |                       |
| extraction  | dB(A)                 | 72            |                       |
| Heat emission   |                       |               |                       |
| % of installed power, max   |                       | 5             |                       |
| Shipping data**   |                       |               |                       |
|   | net, kg               | 100           |                       |
| Shipping volume   | m <sup>3</sup>        | 0.46          |                       |
| Accessories   |                       |               |                       |
| Stacking kit with QuickDry QDC  |                       | x             |                       |
| Stainless base, 290 mm, and galvanised base for stacking installation, 100 mm |                       | x             |                       |
| Dimensions in mm  |                       |               |                       |
| A1  | Width                 | 595           |                       |
| A2  | Width                 | 735           |                       |
| B   | Depth                 | 974           |                       |
| C   | Height                | 832           |                       |
| D   |                       | 306           |                       |
| E   |                       | 641           |                       |
| F   |                       | 84            |                       |
| G   |                       | 194           |                       |
| H   |                       | 48            |                       |
| I   |                       | 65            |                       |
| J   |                       | 78            |                       |
| K   |                       | 120           |                       |
| L   |                       | 119           |                       |
| M   |                       | 501           |                       |
| N   |                       | 681           |                       |
| O   |                       | 764           |                       |
| 1   | Control panel         | 5             | Hot water             |
| 2   | Door opening ø 255 mm | 6             | Drain valve           |
| 3   | Detergent box         | 7             | Drain pump            |
| 4   | Cold water            | 8             | Electrical connection |
|   |                       | 9             | Payment system        |

\* Other voltages available, see installation manual.

\*\* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

